Application No. 10/568,487

March 5, 2009

Reply to the Office Action dated December 23, 2008

Page 2 of 12

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the

application:

LISTING OF CLAIMS:

Claims 1-18 (canceled).

Claim 19 (currently amended): A saddle riding type-vehicle comprising:

a head pipe that supports a steering shaft so as to rotate freely;

a body frame including a main frame that is connected to the head pipe and

extends obliquely downward to the rear of the vehicle, and a pair of left and right subframes that are connected to the main frame and extend obliquely downward to the

rear; and

a motor supported by and suspended from the main frame and the subframes

such that the motor is not supported from below.

Claim 20 (currently amended): The saddle riding type-vehicle according to claim

19, wherein a connecting portion of the main frame and the subframes is located ahead

of a portion of the main frame supporting the motor.

Claim 21 (currently amended): The saddle riding type-vehicle according to claim

19, wherein the head pipe is connected to a front end of the main frame, and a cross

sectional area of the main frame changes along a longitudinal direction of the main

frame such that the front end is larger than a rear end of the main frame.

Claim 22 (currently amended): The saddle riding type-vehicle according to claim

19, wherein the main frame supports the motor at a rear end of the main frame.

Application No. 10/568,487 March 5, 2009 Reply to the Office Action dated December 23, 2008 Page 3 of 12

Claim 23 (currently amended): The saddle riding type-vehicle according to claim 19, wherein the subframes include bent portions which are bent convexly downward and support the motor at least in one location adjacent the bent portions.

Claim 24 (currently amended): The saddle riding type-vehicle according to claim 19, wherein the subframes include bent portions which are bent convexly downward and support the motor at least in one location further toward a rear of the subframes than the bent portions.

Claim 25 (currently amended): The saddle riding type-vehicle according to claim 19, further including a rear wheel and rear arms supporting the rear wheel and extending substantially in a front to rear direction, wherein the subframe is bent convexly downward, wherein both a portion of the motor and the rear arms are supported at rear ends of the subframes.

Claim 26 (currently amended): The saddle riding type-vehicle according to claim 19, further comprising rear side frames extending obliquely upward toward the rear of the vehicle, wherein the subframes include bent portions bent convexly downward and the rear side frames are connected to a portion of the subframes further toward the rear than the bent portions.

Claim 27 (currently amended): The saddle riding type-vehicle according to claim 19, further including plural rear side frames extending obliquely upward to the rear of the vehicle, wherein the rear side frames are connected to one another and to rear ends of the subframes.

Application No. 10/568,487 March 5, 2009 Reply to the Office Action dated December 23, 2008 Page 4 of 12

Claim 28 (currently amended): The saddle riding type-vehicle according to claim 27, wherein the subframes support the motor at least in one location adjacent connecting portions to which the rear side frames are connected to the subframes.

Claim 29 (currently amended): The saddle riding type-vehicle according to claim 19, wherein the motor is an internal combustion engine having a crankcase and a cylinder that extends obliquely upward toward the front of the vehicle from the crankcase, and the cylinder is connected to the main frame and the crankcase is connected to the subframes.

Claim 30 (currently amended): The saddle riding type-vehicle according to claim 29, wherein an axis of the cylinder extends obliquely upward toward the front of the vehicle, the subframes include bent portions bent convexly downward, and front portions of the subframes forward of the bent portions extend substantially parallel to the axis of the cylinder.

Claim 31 (currently amended): The saddle riding type-vehicle according to claim 29, wherein an axis of the cylinder extends obliquely upward to the front of the vehicle, the subframes include bent portions bent convexly downward, and the bent portions of the subframes are located above a portion of the cylinder and the crankcase in the internal combustion engine.

Claim 32 (currently amended): A saddle riding type-vehicle comprising: a head pipe that supports a steering shaft so as to rotate freely; a body frame including a main frame that is connected to the head pipe and extends obliquely downward to the rear of the vehicle, and a pair of left and right subframes that are connected to the main frame and extend obliquely downward to the rear; and

Application No. 10/568,487

March 5, 2009

Reply to the Office Action dated December 23, 2008

Page 5 of 12

a motor supported <u>and suspended</u> in two locations spaced in a front to rear direction along by each of the respective subframes <u>such that the motor is not</u> supported from below.

Claim 33 (currently amended): The saddle riding type-vehicle according to claim 32, wherein the motor is an internal combustion engine including a crankcase and a cylinder that extends obliquely upward to the front of the vehicle from the crankcase, and the cylinder is connected to the main frame and the crankcase is connected to the subframes.

Claim 34 (currently amended): A saddle riding type-vehicle comprising:

a head pipe that supports a steering shaft so as to rotate freely;

a body frame that extends obliquely downward to the rear of the vehicle from the head pipe, the body frame including at least a pair of left and right side frames;

a motor supported by <u>and suspended from</u> the body frame <u>such that the motor is</u> <u>not supported from below;</u>

a rear wheel and rear arms supporting the rear wheel and extending substantially in a front to rear direction;

left and right brackets fixed to the left and the right side frames, respectively; and a pivot shaft that penetrates through both the left and right brackets, both the rear arms, and the motor, wherein the pivot shaft attaches both the rear arms and the motor to both the brackets in a state in which the left and the right brackets are interposed between the left and the right rear arms and the motor, respectively.

Claim 35 (currently amended): The saddle riding type-vehicle according to claim 34, wherein the body frame includes a main frame that is connected to the head pipe and extends obliquely downward to the rear, and a pair of left and right subframes that

Application No. 10/568,487 March 5, 2009 Reply to the Office Action dated December 23, 2008 Page 6 of 12

are connected to the main frame and extend obliquely downward to the rear, and the side frames include the subframes.

Claim 36 (currently amended): The saddle riding type-vehicle according to claim 35, wherein a portion of the motor is supported by the main frame.

Claim 37 (currently amended): The saddle riding type-vehicle according to claim 35, further comprising an air cleaner and a battery, wherein the air cleaner and the battery are arranged in a front to rear direction of the vehicle.